# Somfy SDN Cable

Lancaster offers the Somfy SDN composite control and power cable to its trade partners including Interior Designers, Architects, Institutional Buyers, Independent Workrooms and A/V Companies.

This yellow SDN low-voltage-motor power and data cable for Sonesse Ultra 50 and Sonesse 30 is now available in 100', 500', and 1,000' reels from Lancaster & Associates. This equates to significant budget savings for smaller-scale installations, and eliminates the waste and warehousing of excess materials (and cash flow) by ordering the right size for your project.

# SOMFY SDN NonPlenum Features & Specifications

#### Applications

Somfy Systems plenum control cable Plenum RS-232C, RS-485 simplex data and control

Plenum control and communication cable

#### Component I:

22 AWG data triad

7-strand annealed bare copper conductors

Foam fluorinated ethylene propylene insulation

Alum/poly shield foil in 24 AWG 7-strand tinned copper drain wire

#### Electrical

22 AWG DCR: 16.6  $\Omega$  / 1000' | 54.2  $\Omega$ /KM Mutual capacitance: 12.0 pF/FT | 39.4 pF/M Shield DCR: 22.5  $\Omega$  / 1000' | 73.8  $\Omega$ /KM Impedance: 107  $\Omega$  Voltage rating: 300V 14 AWG DCR: 2.07  $\Omega$  / 1000' | 6.79  $\Omega$ /KM Maximum current: 8A@25°C

#### Component 2:

14 AWG power pair

41-strand annealed bare copper conductors Plenum rated polyvinyl chloride insulation

#### Installation

Pull Tension: 86 Lbs | 383 N

Bend radius: 2.66" | 68mm unloaded Bend radius: 5.32" | 136mm loaded

Plenum cable should be conditioned at room temperature for 24 hours prior to installation and never installed below 32°F | 0°C ambient temperature

# **SOMFY SDN Plenum Features & Specifications**

#### **Applications**

Somfy Systems control cable

Non-plenum RS-232C, RS-485 simplex data and control

Non-plenum control and communication cable

#### Component I:

22 AWG data triad

7-strand annealed bare copper conductors

Foamed polyethylene insulation

Alum/poly shield foil in 24 AWG 7-strand tinned copper drain wire

#### Electrical:

22 AWG DCR: 16.6  $\Omega$  / 1000' | 54.2  $\Omega$ /KM Mutual capacitance: 12.5 pF/FT | 41.0 pF/M Shield DCR: 22.5  $\Omega$  / 1000' | 73.8  $\Omega$ /KM Impedance: 100  $\Omega$  Voltage rating: 300V 14 AWG DCR: 2.07  $\Omega$  / 1000' | 6.79  $\Omega$ /KM Maximum current: 8A@25°C

#### Component 2:

14 AWG power pair

41-strand annealed bare copper conductors

Semi-rigid polyvinyl chloride insulation

#### Installation

Pull Tension: 86 Lbs | 383 N


Bend radius: 2.84" | 73mm unloaded

Bend radius: 5.68" | 145mm loaded



# Somfy SDN List Pricing

Somfy SDN cable is the perfect complement to Somfy's Digital Network, the latest generation of bus-line enabled Intelligent Tubular Motors and Smart Switch Controls. The SDN components are integrated into a cost effective system designed to operate a wide range of end products such as solar screens, projection screens and Venetian blinds over a standard RS-485 network.




Lancaster & Associates Standard Terms of Sale apply to all prices. All prices include packaging and UPS Ground freight charge. Orders received by 1:30 p.m. CST will ship same day. Prices and design modifications are subject to change without notice.

### SOMFY SDN CABLE PRICING


# SOMFY SDN CABLE, NON-PLENUM

Product SKU	Ft/Roll	Price*
SOM-9020126.0100	100'	118.00
SOM-9020126.0500	500'	333.00
SOM-9020126.1000	1,000'	534.00



# SOMFY SDN CABLE, PLENUM

Product SKU	Ft/Roll	Price*
SOM-9020127.0100	100'	159.00
SOM-9020127.0500	500'	454.00
SOM-9020127.1000	1,000'	731.00



<sup>\*</sup>Pricing including packaging and UPS Ground Freight Charges

### EXPEDITED SHIPPING CHARGES

UPS 2nd Day	Price
100' Roll	45.00
500' Roll	140.00
I,000' Roll	310.00
UPS Next Day	Price
100' Roll	95.00
500' Roll	190.00
1,000' Roll	365.00

Orders received by 1:30 p.m. CST will ship same day

## Packaging Dimensions

0		
100' roll	$10" \times 10" \times 10"$	5lbs
500' roll	$10" \times 10" \times 10"$	25lbs
1000' roll	$16" \times 16" \times 16"$	60lbs

